COATING REMOVER



Heavy Duty Coating And Epoxy Grout Haze Remover

PTU Coating Remover is a multipurpose floor coating remover. Removes acrylic, urethane, epoxy, and most UV coatings.

- Remove tough epoxy grout haze on tile and grout projects.
- Formulated with readily-biodegradable materials
- Effective on the toughest to remove finishes and coatings.



Pre-Application

Floor should be swept or vacuumed to remove loose debris and grit

Epoxy Grout Haze Removal

Start at 1:3 parts water and test, can be used up to a 1:1 ratio

Application

- 1. Using mop and bucket, apply liberally to surface
- 2. Allow to dwell for approximately 20-30 minutes (do not allow to solution to dry, rewet if needed)
- 3. Agitate area with stiff bristle brush
- 4. Repeat process if needed
- 5. Once removed, remove slurry and rinse thoroughly (multiple rinses may be needed) with XL PTU Coating Prep.
- 6. Allow to dry completely

Coating Removal

Start at 1:4 parts water and test, can be used up to a 1:1 ratio

Application

- 1. Using mop and bucket, apply liberally to surface
- 2. Allow to dwell for approximately 15-20 minutes (do not allow solution to dry, rewet if needed)
- 3. Using a rotary floor machine with appropriate pad or brush, agitate area
- 4. Repeat process if needed
- 5. Remove slurry with wet vacuum or auto scrubber
- 6. Rinse with fresh clean water or XL PTU Coating Prep.
- 7. Allow to dry completely

Note

Caution is needed when working on wet floors

All Rights Reserved. © 2022 • #TDS2022-CR1