

PRO-TECT ULTRA RESILIENT MATTE



Restores The Matted Appearance Of Luxury Vinyl Floors

Designed to respect the original appearance of the flooring, this easy-to-apply, durable coating helps to restore the original look and appeal of your flooring.

- Designed for demanding, high traffic areas
- Highly resistant to scratch, mar, and heavy foot traffic
- Natural, easy application, high coverage rate



Pre-Application

Prior to application, the space should be conditioned and between 60-80 degrees Fahrenheit. Surface should be properly prepared and cleaned.

1. All acrylic finishes should be removed
2. Any existing urethane coating showing flaking, or yellowing should be removed
3. Surface should be agitated using a 3M Scotch-Brite Surface Preparation Pad Plus (SPP) pad (or equivalent)
4. Floor must be final cleaned using XL PTU Coating Prep for proper adhesion to occur

Mixing

1. Shake PTU Resilient Matte bottle thoroughly to suspend any settlement
2. Allow mixture to settle for 5 minutes before use

Application

1. Pre-charge your 3m Scotchgard Floor protector applicator pad (Blue) or equivalent with PTU Resilient Matte
2. Apply PTU Resilient Matte in manageable puddles or streams to the floor. For best results, apply material in a linear direction "Box Pattern" as opposed to figure 8 or swirl completely covering the area with a very thin coat
3. Allow coating to dry (depending on temperature and humidity approximately 45-60 minutes)
4. Apply second coat (if needed) opposite direction as the first.
5. Allow coating to dry for at least 2 hours prior to re-opening space for use. (Do not scrub or mop the floor for at least 48 hours after application of coating)
6. Wait 24 hours before moving furniture in

Maintenance of coating:

There is no better way to maintain the appearance of your flooring than to have in place a well-designed maintenance program, including proper walk off matting. As with any coating or finish, daily maintenance is recommended to remove debris that may have the potential to abrade the surface.

Daily – Dust mop and spot damp mop as needed

Routine maintenance – Neutral cleaner like XL APC or XL LVT/Wood Floor Cleaner, white pad (or equivalent brush)

Periodic cleaning – Neutral cleaner Like XL APC or XL LVT/Wood Floor Cleaner with red pad (or equivalent brush)

Deep/restorative – Neutral cleaner like XL APC with red or blue pad (or equivalent brush)

Re-coating – when needed, abrad the surface using a 3m SPP pad (or equivalent) and follow the coating steps above.