

PRO-TECT ULTRA

COATING REMOVER



Heavy Duty Coating And Epoxy Grout Haze Remover

PTU Coating Remover is a multipurpose floor coating remover. Removes acrylic, urethane, epoxy, and most UV coatings.

- Remove tough epoxy grout haze on tile and grout projects.
- Formulated with readily-biodegradable materials
- Effective on the toughest to remove finishes and coatings.
- Coverage: 1:3 grout haze, 1:8 stripping



Pre-Application

Floor should be swept or vacuumed to remove loose debris and grit

Epoxy Grout Haze Removal

Start at 1:3 parts water and test, can be used up to a 1:1 ratio

Application

1. Using mop and bucket, apply liberally to surface
2. Allow to dwell for approximately 20-30 minutes (do not allow to solution to dry, rewet if needed)
3. Agitate area with stiff bristle brush
4. Repeat process if needed
5. Once removed, remove slurry and rinse thoroughly (multiple rinses may be needed) with XL PTU Coating Prep.
6. Allow to dry completely

Coating Removal

Start at 1:4 parts water and test, can be used up to a 1:1 ratio

Application

1. Using mop and bucket, apply liberally to surface
2. Allow to dwell for approximately 15-20 minutes (do not allow solution to dry, rewet if needed)
3. Using a rotary floor machine with appropriate pad or brush, agitate area
4. Repeat process if needed
5. Remove slurry with wet vacuum or auto scrubber
6. Rinse with fresh clean water or XL PTU Coating Prep.
7. Allow to dry completely

Note

Caution is needed when working on wet floors